

A Smarter Way for Your Broadband Life

Huawei HG8245H, an intelligent routing-type ONT

Smart
service

Smart
interconnection



Smart O&M

○ Device Parameters

Dimensions (L x W x H)	176 mm x 138.5 mm x 28 mm (without an external antenna)
Weight	About 260 g
Operating temperature	0°C to +40°C
Operating humidity	5% RH to 95% RH (non-condensing)
Power adapter input	100–240 V AC, 50/60 Hz
System power supply	11–14 V DC, 1.5 A
Static power consumption	5.5 W
Maximum power consumption	16.5 W
Ports	2POTS + 4GE +2.4G Wi-Fi + 1USB
Indicators	POWER/PON/LOS/LAN/TEL/USB /WLAN/WPS

○ Interface Parameters

GPON Port	<ul style="list-style-type: none">• Class B+• Receiver sensitivity: -27 dBm• Wavelengths: US 1310 nm, DS 1490 nm• WBF• Flexible mapping between GEM Port and TCONT• GPON: consistent with the SN or password authentication defined in G.984.3• Bi-directional FEC• SR-DBA and NSR-DBA
Ethernet Port	<ul style="list-style-type: none">• Ethernet port-based VLAN tags and tag removal• 1:1 VLAN, N:1 VLAN, or VLAN transparent transmission• QinQ VLAN• Limit on the number of learned MAC addresses• MAC address learning
POTS Port	<ul style="list-style-type: none">• Maximum REN: 4• G.711A/μ, G.729a/b and G.722 encoding/decoding• T.30/T.38/G.711 fax mode• DTMF• Emergency calls (with the SIP protocol)
USB Port	<ul style="list-style-type: none">• USB2.0• FTP-based network storage
WLAN	<ul style="list-style-type: none">• IEEE 802.11 b/g/n• 2 x 2 MIMO• Antenna gain: 2 dBi• WMM• Multiple SSIDs• WPS• Air interface rate: 300 Mbps

○ Product Function

Smart interconnection

- Smart Wi-Fi coverage (V300R015C10)
- SIP/H.248 auto-negotiation
- Any port any service
- Parental control (V300R015C00)
- L2/L3(IPv4) forwarding: 1G uplink, 2G downlink

Smart service

- Smart Wi-Fi sharing:
 - Portal/802.1x authentication (V300R015C10)
 - SoftGRE-based sharing (V300R015C10)
- Association of one account with two POTS ports

Smart O&M

- IPTV video quality diagnosis (V300R015C10)
- Variable-length OMCI messages
- Active/Passive rogue ONT detection and isolation
- Call emulation, and circuit test and loop-line test
- PPPoE/DHCP simulation testing
- WLAN emulation

Layer 3 Features

- PPPoE/Static IP/DHCP
- NAT/NAPT
- Port forwarding
- ALG, UPnP
- DDNS/DNS server/DNS client
- IPv6/IPv4 dual stack, and DS-Lite
- Static/Default routes
- Multiple services on one WAN port

Multicast

- IGMP v2/v3 proxy(V300R015C00)/snooping
- MLD v1/v2 snooping
- Multicast services through Wi-Fi

QoS

- Ethernet port rate limitation
- 802.1p priority
- SP/WRR/SP+WRR
- Broadcast packet rate limitation

Security

- SPI firewall
- Filtering based on MAC/IP/URL addresses

Common O&M

- OMCI/Web UI/TR069
- Dual-system software backup and rollback

Power Saving

- Indicator power saving
- Scheduled Wi-Fi shutdown (V300R015C00)