

KX-HDV330

PRODUCTION DISCONTINUED

Specifications

Display

	KX-HDV430	KX-HDV330	KX-HDV230	KX-HDV130	KX-HDV100
LCD Display	4.3 - inch color TFT LCD with touch screen	4.3 - inch color TFT LCD with touch panel	Monochrome Graphical		
LCD Size	-		132 × 64 pixel 2.3 inch Graphical LCD 160 × 384 pixel 5 inch Graphical LCD	132 × 64 pixel 2.3 inch Graphical LCD	
LCD Contrast	-		6 levels		-
LCD Backlight	Active: 8 levels, Inactive: Low / Off		On/Auto/Off		-

Install Options

	KX-HDV430	KX-HDV330	KX-HDV230	KX-HDV130	KX-HDV100
Desk Mount Tilt	Yes – 2 positions				
Wall Mount	- (Included)			KX-A440 (optional)	
Power Adaptor	KX-A424 (optional)	KX-A424 or KX-A422 (Optional)		KX-A423 (optional)	- (Included)

Audio Features

	KX-HDV430	KX-HDV330	KX-HDV230	KX-HDV130	KX-HDV100
Handset, Speaker, Headset Volume	8 levels (includes echo cancellation and distortion prevention)				
Ringtones	27				
Ringer Volume	8 levels + Off				
Headset Port	RJ9 jack				-
Electronic Hook Switch Control Port	3.5 mm			-	
Built-in Bluetooth®	Bluetooth V2.1 (Class1 / HFP)		-		
Audio Codec	G.711a-law / G.711μ-law / G.722 (wideband) / G.729a				
HD Voice	Yes				
Speaker Phone	Yes(Full Duplex / Wideband)	Speaker Phone(Full Duplex / Wideband)		Yes	-

IP Phone for Business

[Home](#) [Support](#)

Programmable Keys	24 (Touch screen on LCD)	24 (Touch Panel on LCD)	24 (12 keys x 2 pages)	2
-------------------	--------------------------	-------------------------	------------------------	---

Software Features

	KX-HDV430	KX-HDV330	KX-HDV230	KX-HDV130	KX-HDV100
Phone Book (Local)	2,500 (500 items x 5 numbers)		500		Up to 500
LDAP Remote Phonebook	Yes				
XML Remote Phonebook	Yes				
Call Log Entries	30 incoming calls + 30 outgoing call		30 incoming calls + 30 outgoing calls		
Conferencing	3 parties (within terminal – multi-party dependent on server)				
XML Application	Yes				-
Music on Hold	Supplied by Host Service (PBX / SIP Server)				

IP Features

	KX-HDV430	KX-HDV330	KX-HDV230	KX-HDV130	KX-HDV100
SIP Accounts	16	12	6	2	1
SIP Compatibility	RFC 3261 Standard SIP Server, Asterisk, Broadsoft, Panasonic IP PBX				
IP Version	IPv6 / IPv4				
DHCP Client	Yes				
DNS	Yes				
HTTP	Yes				
HTTPS	Yes				
SNTP Client	Yes				
VLAN (802.1q)	Yes				
QoS (DiffServ)	Layer 3 ToS DSCP / 802.1p/ Q tagging (VLAN)	Yes			

Configuration

	KX-HDV430	KX-HDV330	KX-HDV230	KX-HDV130	KX-HDV100
Plug & Play Configuration	Server based configuration, TR-069				
Manual Configuration	Internal web Configurator, Local (LCD based) network configuration				

Interface

	KX-HDV430	KX-HDV330	KX-HDV230	KX-HDV130	KX-HDV100
Ethernet Ports	2				1
Ethernet Interface	10/100/1000 Mbps			10/100 Mbps	
PoE (Power over Ethernet)	Yes				-

<p>Power Consumption</p>	<p>PoE Stand-by: approx. 3.9 W (ECO mode off), approx. 3.2 W (ECO mode on) Voice Call: approx. 4.9 W (ECO mode off), approx. 4.1 W (ECO mode on) Video Call: approx. 5.6 W (ECO mode off), approx. 4.9 W (ECO mode on)</p> <p>AC Adaptor Stand-by: approx. 3.9 W (ECO mode off), approx. 3.2 W (ECO mode on) Voice Call: approx. 4.8 W (ECO mode off), approx. 3.9 W (ECO mode on) Video Call: approx. 5.5 W (ECO mode off), approx. 4.7 W (ECO mode on)</p>	<p>PoE Stand-by: approx. 2.7 W (ECO mode off), approx. 2.2 W (ECO mode on) Talking: approx. 3.5 W (ECO mode off), approx. 2.8 W (ECO mode on) Max: 4.4 W</p> <p>AC Adaptor Stand-by: approx. 2.6 W (ECO mode off), approx. 1.9 W (ECO mode on) Talking: approx. 3.4 W (ECO mode off), approx. 2.7 W (ECO mode on) Max: 4.4 W</p>	<p>PoE Stand-by: approx. 3.1 W (ECO mode off), approx. 2.9 W (ECO mode on) Talking: approx. 3.2 W (ECO mode off), approx. 3.0 W (ECO mode on) Max: 4.2 W</p> <p>AC Adaptor Stand-by: approx. 2.8 W (ECO mode off), approx. 2.1 W (ECO mode on) Talking: approx. 2.9 W (ECO mode off), approx. 2.2 W (ECO mode on) Max: 4.2 W</p>	<p>PoE Stand-by: approx. 2.2 W (ECO mode off), 1.9 W (ECO mode on) Talking: 2.3 W (ECO mode off), 2.0 W (ECO mode on) Max: 2.8 W</p> <p>AC Adaptor Stand-by: 2.0 W (ECO mode off), 1.3 W (ECO mode on) Talking: 2.1 W (ECO mode off), 1.4 W (ECO mode on) Max: 2.8 W</p>	<p>AC Adaptor Standby: 0.9 W Talking: 1.0 W Max: 1.8 W</p>
<p>Operating Environment</p>	<p>0 °C - 40 °C (32 °F - 104 °F)</p>				
<p>Dimensions (Width x Depth x Height; excluding the handset, stand attached)</p>	<p>High position: 195 mm x 190 mm x 209 mm Low position: 195 mm x 184 mm x 188 mm</p>		<p>High position: 252 mm x 179 mm x 188 mm (9.9 in x 7.1 in x 7.4 in) Low position: 252 mm x 187 mm x 154 mm (9.9 in x 7.4 in x 6.1 in)</p>	<p>High position: 167 mm x 165 mm x 148 mm Low position: 167 mm x 173 mm x 115 mm</p>	
<p>Weight (with handset,handset cord and stand)</p>	<p>870 g</p>	<p>850 g</p>	<p>1,030 g (2.28 lb)</p>	<p>691 g</p>	<p>672 g</p>

• The Bluetooth word mark is trademark or registered trademark owned by Bluetooth SIG, Inc. and any use of such mark by Panasonic Corporation is under license.

[Print](#)

[Back to Top](#)

[Area / Country](#)

© Panasonic Connect Co.,Ltd.

[Terms of Use](#) | [Web Accessibility Policy](#) | [Privacy Policy](#) | [Cookie Policy](#) | [Panasonic Holdings](#)