



S412 Lite

VoIP PBX

Yeastar S412 Lite is a compact analog and VoIP capable phone system supporting a maximum of 16 users. It comes out-of-box with full PBX features plus enhancing UC capacity with Linkus UC Clients. The easy management, abundant features, and quick provisioning empower S412 Lite to deliver a flexible, convenient, and secure business communications experience.



Specifications

Max Users	16 (8 SIP + 8 FXS)
Max Concurrent Calls	8
VoIP Trunks	4
Max FXS Ports	8 (4 inbuilt)
Max FXO/BRI Ports	4
Max GSM/4G Ports	2
Max 4G Port (Data)	1
External Storage	1 TF Card
Protocol	SIP (RFC3261), IAX2
Transport Protocol	UDP, TCP, TLS, SRTP
Codec	G711 (alaw/ulaw), G722, G726, G729A, GSM, Speex, ADPCM, iLBC, H263, H263P, H264, MPEG4
DTMF	In-band, RFC4733, RFC2833, SIP INFO
IP Services	Static IP, DHCP, VPN, Firewall, VLAN, DDNS, PPPoE, QoS, Static NAT, STUN
Voicemail	5000 min (expandable)
App Center	Linkus, Auto Provisioning, LDAP Server, Conference Panel, VPN Server, Billing App*, Hotel App*, char utile h+ Integration
Power	DC 12V 3.3A
Size (L x W x H) / Weight	29 x 18 x 3.3 cm / 0.68 kg
Environment	Operation Range: 0° C to 40°C, 32° F to 104° F; Humidity: 10-90% non-condensing

Features	
• Linkus UC Clients	• Dial by Name
• Linkus Cloud Service*	• DISA
• Remote Management	• Distinctive Ringtone
• Mobility Extension	• DNIS
• Hot Standby	• DND
• Multisite Interconnect	• Event Center
• Auto Attendant (IVR)	• Fax to Email
• AutoCLIP	• Feature Code
• Auto Provisioning	• Firewall
• Blocklist/Allowlist	• LDAP
• Call Back	• Music on Hold
• Call Forwarding	• Paging/Intercom
• Call Monitor	• PIN List
• Call Parking	• Paging Group
• Call Pickup	• Queue
• Call Recording	• Ring Group
• Call Routing	• SIP Forking
• Call Transfer	• Speed Dial
• Call Waiting	• T.38 Fax
• Caller ID	• Time Condition
• CDR	• Voicemail
• Custom Prompt	• Music
• Conference Call	• Multi-language

*Features with the star mark requires additional licenses.